TS725, TS725W, TS725K

Elite long tights

AVAILABLE SIZES:
2XS-3XL

Design number: 1
Team name / Project name: PROJECT
Designer: DESIGNER

1

95/70/5/0 | WHITE | 100/80/40/40 | 15/5/95/0

SJH
FONT: MYRIAD PRO BOLD

PREVIEW

THIS VISUALIZATION SERVES FOR PREVIEW PURPOSES ONLY, THEREFORE DESIGN, LOGOS AND PLACEMENT MAY VARY IN THE FINAL

1 **Avoid placing artwork across seams.** Please work on ARTWORK layer only. Details that can't be printed are locked. At saving file, turn off visibility for GUIDE layer.

2 Pattern must be filled with the design as this is the main guidance for designers at the pre-print process.

3 We recommend placing any logos or special graphics inside the blue-dotted safe area. Anything placed beyond the safe area will run the risk of being cut out.

FLATLOCK SEAM
SEAM
PATTERN OUTLINE
DESIGN SAFE AREA

Remember that because of the many pieces of each product, designing for apparel is very different than designing for print media. With the exception of the front zipper, do not cross seams with your designs (i.e., front panel to sleeves, front panel to side panels, shorts side panels to back panel.) Because of size variations and seam allowances, we cannot guarantee that designs that cross seams will align correctly.

1) All artwork should be in vector format, including all sponsor logos and design elements. If using raster (pixel based) images please make sure that it has not less than 150dpi at a ctual size(not less than 2500px shortest edge)

2) Please send in separate files all logos. For maximum quality use vector logos (AI, EPS, PDF).

3) Designs must be wider and higher than the given visualisation dimention. Please, do not cut design into the given visualisation details, instead place it under a mask.

4) **Use only RGB colors**. Do not use CMYK or PANTONE. Color profile- ADOBE RGB (1998). Please note that colors that appear on your screen may look very different when printed on fabric. If using Pantone numbers- preferred when specifying colors, but you are welcome to send a color sample if you desire an exact match and no Pantone color is available. Color matching may require additional delivery time for your order.

5) This artwork serves for visualisation and concept purposes only. Please review design sketch carefully and thoroughly. It is the customers responsibilty to make sure there are no mistakes in the artwork.

6) Convert all text to outlines or supply all fonts used in the design. Strokes and lines must be outlined or curved.

7) Do not use overprint.

8) Max file size 30 mb

COLORS:

COLOR PROFILE - ADOBE RGB (1998)

TS725, TS725W, TS725K

Elite long tights

AVAILABLE SIZES:
2XS-3XL

Design number:	1
Team name / Project name:	PROJECT
Designer:	DESIGNER

2

95/70/5/0 | WHITE | 100/80/40/40 | 15/5/95/0

SJH
FONT: MYRIAD PRO BOLD

PREVIEW

THIS VISUALIZATION SERVES FOR PREVIEW PURPOSES ONLY, THEREFORE DESIGN, LOGOS AND PLACEMENT MAY VARY IN THE FINAL

1 **Avoid placing artwork across seams.** Please work on ARTWORK layer only. Details that can't be printed are locked. At saving file, turn off visibility for GUIDE layer.

2 Pattern must be filled with the design as this is the main guidance for designers at the pre-print process.

3 We recommend placing any logos or special graphics inside the blue-dotted safe area. Anything placed beyond the safe area will run the risk of being cut out.

FLATLOCK SEAM
SEAM
PATTERN OUTLINE
DESIGN SAFE AREA

Remember that because of the many pieces of each product, designing for apparel is very different than designing for print media. With the exception of the front zipper, do not cross seams with your designs (i.e., front panel to sleeves, front panel to side panels, shorts side panels to back panel.) Because of size variations and seam allowances, we cannot guarantee that designs that cross seams will align correctly.

1) All artwork should be in vector format, including all sponsor logos and design elements. If using raster (pixel based) images please make sure that it has not less than 150dpi at a ctual size(not less than 2500px shortest edge)

2) Please send in separate files all logos. For maximum quality use vector logos (AI, EPS, PDF).

3) Designs must be wider and higher than the given visualisation dimention. Please, do not cut design into the given visualisation details, instead place it under a mask.

4) **Use only RGB colors**. Do not use CMYK or PANTONE. Color profile- ADOBE RGB (1998). Please note that colors that appear on your screen may look very different when printed on fabric. If using Pantone numbers- preferred when specifying colors, but you are welcome to send a color sample if you desire an exact match and no Pantone color is available. Color matching may require additional delivery time for your order.

5) This artwork serves for visualisation and concept purposes only. Please review design sketch carefully and thoroughly. It is the customers responsibilty to make sure there are no mistakes in the artwork.

6) Convert all text to outlines or supply all fonts used in the design. Strokes and lines must be outlined or curved.

7) Do not use overprint.

8) Max file size 30 mb

COLORS:

COLOR PROFILE - ADOBE RGB (1998)

TS725, TS725W, TS725K

Elite long tights

AVAILABLE SIZES:
2XS-3XL

Design number:	1
Team name / Project name:	PROJECT
Designer:	DESIGNER

3

95/70/5/0 | WHITE | 100/80/40/40 | 15/5/95/0

SJH
FONT: MYRIAD PRO BOLD

PREVIEW

THIS VISUALIZATION SERVES FOR PREVIEW PURPOSES ONLY, THEREFORE DESIGN, LOGOS AND PLACEMENT MAY VARY IN THE FINAL

1 **Avoid placing artwork across seams.** Please work on ARTWORK layer only. Details that can't be printed are locked. At saving file, turn off visibility for GUIDE layer.

2 Pattern must be filled with the design as this is the main guidance for designers at the pre-print process.

3 We recommend placing any logos or special graphics inside the blue-dotted safe area. Anything placed beyond the safe area will run the risk of being cut out.

FLATLOCK SEAM
SEAM
PATTERN OUTLINE
DESIGN SAFE AREA

Remember that because of the many pieces of each product, designing for apparel is very different than designing for print media. With the exception of the front zipper, do not cross seams with your designs (i.e., front panel to sleeves, front panel to side panels, shorts side panels to back panel.) Because of size variations and seam allowances, we cannot guarantee that designs that cross seams will align correctly.

1) All artwork should be in vector format, including all sponsor logos and design elements. If using raster (pixel based) images please make sure that it has not less than 150dpi at a ctual size(not less than 2500px shortest edge)

2) Please send in separate files all logos. For maximum quality use vector logos (AI, EPS, PDF).

3) Designs must be wider and higher than the given visualisation dimention. Please, do not cut design into the given visualisation details, instead place it under a mask.

4) **Use only RGB colors**. Do not use CMYK or PANTONE. Color profile- ADOBE RGB (1998). Please note that colors that appear on your screen may look very different when printed on fabric. If using Pantone numbers- preferred when specifying colors, but you are welcome to send a color sample if you desire an exact match and no Pantone color is available. Color matching may require additional delivery time for your order.

5) This artwork serves for visualisation and concept purposes only. Please review design sketch carefully and thoroughly. It is the customers responsibilty to make sure there are no mistakes in the artwork.

6) Convert all text to outlines or supply all fonts used in the design. Strokes and lines must be outlined or curved.

7) Do not use overprint.

8) Max file size 30 mb

COLORS:

COLOR PROFILE - ADOBE RGB (1998)